



*Rely on it.*

## RENOLIT stretch ceiling films: For unique interior designs

Innovative  
films for the  
processing  
industry





## RENOLIT OFFERS A WIDE RANGE OF COLOURS AND SURFACES








### STOCK RANGE

COLOUR	COLOUR NAME	ARTICLE NUMBER	COLOUR	COLOUR NAME	ARTICLE NUMBER
--------	-------------	----------------	--------	-------------	----------------



#### SUPERMIRROR

	Polarweiss	10.40.75.0045.000
	Weiss	10.40.75.0001.000
	Creme	10.40.75.0002.000
	Beige	10.40.75.0003.000
	Lachs	10.40.75.0004.000
	Rot	10.40.75.0005.000
	Weinrot	10.40.75.0006.000
	Hellgrün	10.40.75.0007.000
	Apfelgrün	10.40.75.0008.000
	Hellblau	10.40.75.0009.000
	Dunkelblau	10.40.75.0010.000
	Braun	10.40.75.0011.000
	Grau	10.40.75.0012.000
	Schwarz	10.40.75.0013.000

#### SATIN MATT

	Weiss	10.40.75.0014.000
	Transluzent	10.40.75.0015.000
	Elfenbein	10.40.75.0016.000
	Creme	10.40.75.0017.000
	Beige	10.40.75.0018.000
	Rosa	10.40.75.0019.000
	Hellgrün	10.40.75.0020.000

#### MATT STELLAR

	Polarweiss	10.40.75.0044.000
	Weiss	10.40.75.0021.000



## PRODUCT RANGE Flexible PVC film: Developed specifically for interior applications

	STOCK ITEMS	PRODUCTION ITEMS
<b>Colour:</b>	■ 23 standard colours (see left)	■ Virtually any colour possible
<b>Surface finish:</b>	■ Supermirror, Satin Matt or Matt Stellar (see left)	■ Supermirror, Satin Matt or Matt Stellar
<b>Flame-proofing:</b>	■ B1 in acc. with DIN 4102-1, or b-s2-d0 in acc. with DIN EN 14716	■ B1 in acc. with DIN 4102-1, or b-s2-d0 in acc. with DIN EN 14716
<b>Special types:</b>		■ BIO-PRUF™ treated available
<b>Heavy metals:</b>	■ Free of heavy metals in acc. with RoHS	■ Certain colours may contain heavy metals in acc. with RoHS. Information available on request.
<b>Film thickness:</b>	■ 170 µm	■ 170 µm
<b>Film width:</b>	■ 2,000 mm	■ 1,500 – 2,000 mm ■ Metallic colours 1,300 mm
<b>Roll length and winding:</b>	■ Matt: 100 m, face side on inside ■ Gloss: 2 x 50 m, gloss side wound onto gloss side	■ Matt: 300 m, face side on inside ■ Gloss: 2 x 150 m, gloss side wound onto gloss side
<b>Cores:</b>	■ Steel core, internal diameter 76 mm	■ Steel core, internal diameter 76 mm
<b>Packaging:</b>	■ Individual boxes on non-returnable wooden pallet	■ Individual boxes on non-returnable wooden pallet
<b>Minimum order quantity:</b>	■ 100 m (1 roll)	■ 3,000 m (2,100 m subject to surcharge)

## PROOF OF ORIGIN

Each roll provided with lasered and numbered RENOLIT hologram (4.2 x 1.6 cm)



With regard to storage, handling and processing, please see our specifications and handling recommendations.

This information on RENOLIT products is based on the knowledge currently available to us. Information on mechanical characteristics is based on tests which are considered to be reliable. The values listed here are typical values and are not to be adopted into customers' specifications. They serve solely as a source of information and are provided without any guarantee. As such, they do not establish a warranty in any form. We reserve the right to undertake technical modifications. This information may only be published in whole or in part with the prior consent of RENOLIT.

## QUALITY ASSURANCE



- Made in Germany: All stretch ceiling films are produced in Germany.
- Certified QM system (in acc. with DIN EN ISO 9001:2008)
- RoHS directive compliance
- No use of biocides or fungicides
- Certified b-s2-d0 in acc. with DIN EN 14716
- Certified low heavy metal migration
- Certified low water vapour permeability
- Certified low emissions, class A+



### RENOLIT – The company

The RENOLIT Group is an international leader in the manufacture of high-quality plastic films and related products for technical applications. This independent family-owned business, which has been setting benchmarks for quality and innovation for over 70 years, now employs a workforce of approximately 4,500 employees at more than 30 production sites and sales entities. The RENOLIT brand enjoys a worldwide reputation for technical expertise, modern product design and customer-oriented service.

RENOLIT SE  
 Business Unit  
 RENOLIT PROFESSION  
 Horchheimer Straße 50  
 67547 Worms | Germany

Phone: +31.13.5186886  
 Fax: +31.13.5182188  
 stretch-ceiling@renolit.com  
 www.renolit.com

vinyl<sup>plus</sup>



Rely on it.